

SEDIMENT CONTROL NOTES:

- 1. PERIMETER SEDIMENT CONTROLS ARE NECESSARY AT DOWN SLOPING PROPERTY AND STREET EDGES. SEDIMENT CONTROLS MUST PROVIDE CONTAINMENT BY TURNING PERIMETER CONTROLS UPSLOPE INTO PROPERTY.
- 2. PERIMETER CONTROLS CAN INCLUDE MULCH SOCKS, MULCH BERMS AND/OR SILT FENCE PROPERLY TRENCHED IN AND STAKED OR STABILIZED.

EROSION CONTROL NOTES:

- 1. SITE HAS A MINIMUM OF 4" TOPSOIL FOR FINAL STABILIZATION
- 2. CONSTRUCTION ENTRANCE SHALL BE 1"-3" CLEAN ROCK AT A MINIMUM DEPTH OF 6" PER DETAIL EC-3
- SLOPES GREATER THAN 4:1 NEED FIBER BLANKETS AND TEMPORARY OR PERMANENT SEEDING
- 4. SWALES NEED CHECK DAMS OR BLANKETS

EROSION CONTROL FOR RESIDENTIAL LOTS

Plate No. EC-7



2014 STANDARD DETAIL PLATE

City of Blaine - Community Standards